



SWC 32 PRO

Magnet-Kernbohrmaschinen Magnetic Core Drilling Machine



ERGONOMIC
HANDLES



50 μ l HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



SPECIFICATIONS

Motor power	1100 watt
Spindle	19 mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø35 mm
Broach cutter (50mm length)	Ø12 mm - Ø35 mm
RPM	450 min ⁻¹
Weight	10 kg (22,0 lbs)
Magnet power	10000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz



STANDARD ACCESSORIES





ERGONOMIC
HANDLES



50 μ m HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



SPECIFICATIONS

Motor power	1200 watt
Spindle	19 mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø40mm
Broach cutter (50mm length)	Ø12 mm - Ø40 mm
Twist Drill	Upto Ø13 mm
RPM	450 min ⁻¹
Weight	12 kg (26,8 lbs)
Magnet power	10000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz

SWC 40 PRO

Magnet-Kernbohrmaschinen Magnetic Core Drilling Machine




STANDARD ACCESSORIES





SWC 50 MAX-PRO

Magnet-Kernbohrmaschinen Magnetic Core Drilling Machine



ERGONOMIC
HANDLES



50 μ HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



SPECIFICATIONS

Motor power	1350 watt
Spindle	MT 3, 19 mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø50mm
Broach cutter (50mm length)	Ø12 mm - Ø50 mm
Twist Drill	Upto Ø18 mm
RPM	n250 min ⁻¹ - n450 min ⁻¹
Weight	12 kg (26,8 lbs)
Magnet power	11000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz



STANDARD ACCESSORIES

